

## Environmental Monitoring Sensor, Temperature, Humidity, Contact-Closure Inputs for Use with TLNETCARD

MODEL NUMBER: TLNETEM



Ensure ideal environmental conditions with remote monitoring of ambient temperature, humidity and contact-closure status on compatible SmartPro® or SmartOnline® UPS systems operating with a TLNETCARD.

### Description

Connect a TLNETEM module to a Tripp Lite TLNETCARD on a compatible UPS system and gain the ability to monitor your network's environmental conditions from anywhere in the world. The TLNETEM contains a temperature and humidity sensor as well as a dry contact interface to monitor up to four compatible devices, such as smoke detectors, fire alarms and security systems.

By ensuring the optimum environment in your network closet or data center, the TLNETEM helps prevent equipment failure and costly downtime caused by excessive heat and high-humidity conditions.

### Features

#### Remotely Monitor Your Network Environment

- Allows users to remotely monitor temperature and humidity in network environments
- Helps prevent equipment degradation and failure
- Dry-contact interface enables monitoring of up to four alarm, security and telecom devices

#### Versatile and Easy Installation

- Integrates easily with a Tripp Lite SmartPro or SmartOnline UPS System operating with a TLNETCARD web management accessory
- Extra-long cable allows the sensor to be mounted up to 12 ft. away from the TLNETCARD

#### TAA Compliant

### Highlights

- Environmental Monitoring Sensor for use with Tripp Lite TLNETCARD enabled UPS systems
- Reports the ambient temperature, humidity and contact closure status of up to four compatible devices
- Simple installation and integration into existing compatible systems
- TAA compliant

### System Requirements

- Compatible Tripp Lite SmartPro or SmartOnline UPS system with a TLNETCARD installed
- Web browser or terminal emulator

### Package Includes

- TLNETEM Environmental Monitoring Sensor
- Owner's Manual



- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

OVERVIEW	
UPC Code	037332191687
Power Management Type	Network Interfaces
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.650 x 6.060 x 6.380
Shipping Dimensions (hwd / cm)	4.19 x 15.39 x 16.21
Shipping Weight (lbs.)	0.5500
Shipping Weight (kg)	0.25
CERTIFICATIONS	
Approvals	TAA Compliant
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>