


# S200 – 50

200 Watts, 50 Volts, Class AB or C  
Milcom 1.5 - 30 MHz

<p><b>GENERAL DESCRIPTION</b> The S200-50 is a COMMON EMITTER, HF, SSB device intended for operation from a 50 Volts supply. It may be operated in Class A, AB or C. The device exhibits excellent linearity and ruggedness.</p>	<p><b>CASE OUTLINE</b> <b>55HX, Style 2</b></p> 
<p><b>ABSOLUTE MAXIMUM RATINGS</b></p> <p>Maximum Power Dissipation @ 25°C                      320 Watts</p> <p><b>Maximum Voltage and Current</b></p> <p>BVces    Collector to Emitter Voltage                      110 Volts BVebo    Emitter to Base Voltage                              4.0 Volts Ic         Collector Current                                        30 A</p> <p><b>Maximum Temperatures</b></p> <p>Storage Temperature                                         - 65 to +150°C Operating Junction Temperature                            +150°C</p>	

## ELECTRICAL CHARACTERISTICS @ 25 °C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
<b>Pout</b>	Power Output	F = 30 MHz	200			Watts
<b>Pin</b>	Power Input	Vcc = 50 Volts			12	Watts
<b>Pg</b>	Power Gain	Class C Bias	12	14.5		dB
<b>ηc</b>	Efficiency			60		%
<b>VSWR</b>	Load Mismatch Tolerance				30:1	


<b>BVebo</b>	Emitter to Base Breakdown	Ie = 20 mA	4.0			Volts
<b>BVces</b>	Collector to Emitter Breakdown	Ic = 100 mA	110			Volts
<b>BVceo</b>	Collector to Emitter Breakdown	Ie = 200 mA	70			Volts
<b>Cob</b>	Output Capacitance	Vcb = 50V, F = 1 MHz		300		pF
<b>hFE</b>	DC - Current Gain	Vce = 5 V, Ic = 1 A	10			
<b>θjc</b>	Thermal Resistance				.55	°C/W

Rev. A August 2005




# S200-50


DC SAFE OPERATING AREA




POWER OUTPUT vs POWER INPUT



IMD vs Pout





Icq vs Vbe



Advanced Power Technology reserves the right to change, without notice, the specifications and information contained herein. Visit our web site at [www.advancedpower.com](http://www.advancedpower.com) or contact our factory direct.

Zin vs FREQUENCY






DIM	MILLIMETER	±TOL	INCHES	±TOL
A	24.76	.13	.975	.005
B	18.42	.13	.725	.005
C	45°	5°	45°	5°
D	6.35	.13	.250	.005
E	3.17	.13	.125	.005
F	5.71	.13	.225	.005
G	12.70	.13	.500 DIA	.005
H	6.60	REF	.260	REF
I	0.13	.02	.005	.001
J	4.32	.25	.170	.010
K	2.59	.25	.102	.010
M	31.75	MAX	1.250	MAX

**STYLE 1:**  
 PIN1 = COLLECTOR  
 2 = BASE (2X)  
 3 = EMITTER

**STYLE 2:**  
 PIN1 = COLLECTOR  
 2 = EMITTER (2X)  
 3 = BASE



DWG NO.

55HX